
























PRODUCT PROFILES		PRODUCT SPECIFICATIONS							
			DECRA VILLA TILE	DECRA TILE	DECRA SHINGLE XD[®]	DECRA SHAKE XD[®]	DECRA SHAKE		
DECRA VILLA TILE	DECRA TILE	Min Roof Pitch ▶	3:12	3:12	4:12	3:12	3:12		
		Panel Size ▶	17" x 44-1/4"	16-1/2" x 52"	14-1/8" x 52-3/8"	14-1/8" x 52-1/8"	14-5/8" x 53"		
DECRA SHINGLE XD	DECRA SHAKE XD	Installed Exposure ▶	14-1/2" x 39-1/2"	14-1/2" x 50"	12-1/4" x 49-1/2"	12-3/8" x 49-7/8"	12-5/8" x 51"		
		Panels per Square ▶	25.2	20	23.8	23.4	22.4		
DECRA SHAKE		Installed Weight ▶	160 lbs. / sq.	150 lbs. / sq.	150 lbs. / sq.	150 lbs. / sq.	150 lbs. / sq.		
AVAILABLE COLORS (Final color selection should be made from an actual product sample)									
DECRA VILLA TILE									
<i>Amalfi Sand</i>		<i>Capri Clay</i>		<i>Pompeii Ash</i>		<i>Rustico Clay</i>		<i>Venetian Gold</i>	
DECRA TILE									
<i>Charcoal</i>		<i>Chestnut</i>		<i>Garnet</i>		<i>Granite Grey</i>		<i>Shadowwood</i>	
<i>Terracotta</i>		<i>Weathered Timber</i>		<i>Tuscan Sun</i>					
DECRA SHINGLE XD									
<i>Classic Cobblestone</i>		<i>Midnight Eclipse</i>		<i>Natural Slate</i>		<i>Old Hickory</i>		<i>Woodland Green</i>	
DECRA SHAKE XD									
<i>Antique Chestnut</i>		<i>Pinnacle Grey</i>		<i>Woodland Green</i>		<i>Midnight Eclipse</i>			
DECRA SHAKE									
<i>Charcoal</i>		<i>Chestnut</i>		<i>Granite Grey</i>		<i>Shadowwood</i>		<i>Weathered Timber</i>	

WARRANTY/COMPOSITION

Warranties

- Lifetime Limited Warranty*
- 120 mph Wind Speed Warranty
- Hail Stone Penetration Warranty

Composition

- Steel – Aluminum-Zinc Hot Dip Coating
- Acrylic Priming System
- Acrylic Basecoat
- Ceramic Coated Stone Granules
- Acrylic Over-Glaze

*DECRA offers a Lifetime Limited Warranty on single family residential in the U.S. & Canada.

DECRA Products Meet Requirements For: International Code Council (IRC, IBC Codes)

- INCLUDES: [City of Los Angeles \(LARC, LABC\)](#)
[California State \(CRC, CBC\)](#)
- [ESR-2901 – Tile, Shake, Shingle Plus \(battens\)](#)
 - [ESR-1754 – Villa Tile, Shake XD, Shingle XD, Shingle Plus \(direct to deck\)](#)

Miami - Dade County, Florida

- [Miami Dade County NOA#18-1015.06 Tile, Villa Tile, Shake, Shingle Plus, Shake XD](#)
- [Miami Dade County NOA#17-1227.02 DECRA Ridge Vent](#)

Florida Building Code

- [Approval #9759-R9: Shake, Tile, Shingle XD, Shake XD, Villa Tile, Shingle Plus](#)
- [Installation: FL11255-R6 2017](#)
- [DECRA Ridge Vent: FL17492-R3 II NOA 17122702 2017](#)

Texas Department of Insurance

- [Products Qualifying for Impact Resistant Roofing Credits](#)
- [Roofing Installation Information and Certification for Reduction in Residential Insurance Premiums](#)
- [TDI Report #RC-282 Wind Resistance – Villa Tile](#)

- [TDI Report #RC-235 Wind Resistance – Shake XD, Shingle XD](#)
- [TDI Report #RC-281 Wind Resistance – Tile, Shake, Shingle Plus](#)

Underwriters Laboratories, Inc – Listings File #R14710

- Fire – UL 790 (ASTM E108 – A, B & C)
- Fire – UL CAN/ULC-S107 (Canada)
- Hail – UL 2218 (Class 4)
- Uplift – UL 580 & UL 1897 – Class 90

Additional Testing for LEED[®] and CA Title 24 Cool Colors

- ASTM – E903 Solar Absorptance, Reflectance, and Transmittance of Materials Using Integrating Spheres
- ASTM – E408 Total Normal Emittance of Surfaces Using Inspection-Meter Techniques
- ASTM – E1980 Calculating Solar Reflectance Index of Horizontal and Low-Sloped Opaque Surfaces

ISO Management System Compliance

- [ISO 9001:2015 Quality Management System](#)
- [ISO 14001:2015 Environmental Management System](#)
- [ISO 45001:2018 Occupational Health & Safety Management System](#)

National Building Code of Canada

- [CCMC Evaluation Report #13551-R \(direct-to-deck\)](#)
- [CCMC Evaluation Report #10241-R \(on battens\)](#)